

Argus Troffer

Description:

The Argus Troffer seamlessly combines advanced lens construction, a versatile design, and long-lasting performance to provide an ideal lighting solution for facilities with limited plenum height.

- PMMA lens with a prismatic diffuser provides consistent, glare-free illumination with exceptional durability and eliminates the risk of discoloration over time
- 9-in-1 design (3 CCT's and 3 wattage's field selectable)
- Slim design (1.97" in height) enables installation in spaces with limited plenum height

Technical Specifications:

Construction: Aluminum frame in a white finish with a steel die-formed back, backlit LEDs

Warranty: 5 Years (labor not included)

PF: >0.9 **THD:** <20%

CRI: >80

Rated Voltage: 120-277 VAC

Dimming: 0-10V (5%-100%)

Lifetime: L70: >60,000 hours

Certifications:














Model No.	Size	Power	Efficacy	Lumens	Field Adjustable CCT	Weight
AB-22-23	2' x 2'	20/25/30	125 lm/w	2,500 / 3,125 / 3,750	3,500 K 4,000 K 5,000 K	5.28 lbs
AB-22-24	2' x 2'	20/30/40	125 lm/w	2,500 / 3,750 / 5,000		5.28 lbs
AB-14-24	2' x 4'	20/30/40	125 lm/w	2,500 / 3,750 / 5,000		6.27 lbs
AB-24-34	1' x 4'	30/35/40	125 lm/w	3,750 / 4,375 / 5,000		8.80 lbs
AB-24-35	1' x 4'	30/40/50	125 lm/w	3,750 / 5,000 / 6,250		8.80 lbs




Dimensions



Size (FT)	LxWxH		
2x2	23.74"x23.74"x1.97"		
1x4	47.76"x11.93"x1.97"		
2x4	47.76"x23.74"x1.97"		

Photometry



Packing Quantities



Carton: 20pcs



Pallet: 64pcs



20ft Container: 1,000pcs

40ft Container: 2,800pcs